

# TWISTED FINGERSTRIPS 2400

These fingerstrips are electronic gaskets for general EMI-shielding applications where there is a narrow opening or gap



## TWISTED FINGERSTRIPS 2401

| Part nr. | A    | C   | D   | F   | G   | H   | Material thickness |
|----------|------|-----|-----|-----|-----|-----|--------------------|
| 2401-01  | 12.3 | 4.6 | 1.8 | 610 | 4.2 | 3.8 | 0.08mm             |
| 2401-02  | 12.3 | 4.8 | 1.8 | 499 | 4.2 | 3.8 | 0.08mm             |

Material: Beryllium copper

| Part nr. | A   | B   | C   | D    | F   | G   | H   | Material thickness |
|----------|-----|-----|-----|------|-----|-----|-----|--------------------|
| 2403-01  | 3.9 | 2.1 | 0.8 | 0.08 | 610 | 2.4 | 2.0 | 0.08mm             |
| 2403-02  | 3.9 | 2.1 | 0.8 | 0.08 | 610 | 2.4 | 2.0 | 0.08mm             |

Material: Beryllium copper

## TWISTED FINGERSTRIPS 2402

| Part number | A   | D   | F     | G   | H   | Material thickness |
|-------------|-----|-----|-------|-----|-----|--------------------|
| 2402-01     | 5.8 | 0.8 | 610   | 2.4 | 2.0 | 0.08mm             |
| 2402-02     | 8.5 | 1.8 | 610   | 4.2 | 3.8 | 0.08mm             |
| 2402-04     | 5.8 | 0.8 | 500   | 2.4 | 2.0 | 0.08mm             |
| 2402-05     | 5.8 | 0.8 | 10000 | 2.4 | 2.0 | 0.08mm             |
| 2402-06     | 8.5 | 1.8 | 406   | 4.2 | 3.8 | 0.08mm             |
| 2402-07     | 8.5 | 1.8 | 499   | 4.2 | 3.8 | 0.08mm             |
| 2402-08     | 8.5 | 1.8 | 10000 | 4.2 | 3.8 | 0.08mm             |

Material: Beryllium copper

## TWISTED FINGERSTRIPS 2404

| Part nr. | A   | B   | C   | D   | F   | G   | H   | Material thickness | Compression force N        |
|----------|-----|-----|-----|-----|-----|-----|-----|--------------------|----------------------------|
| 2404-04  | 4.3 | 1.5 | 4.4 | 0.8 | 405 | 2.4 | 2.0 | 0.08mm             |                            |
| 2404-09  | 5.9 | 1.5 | 4.3 | 0.8 | 405 | 2.4 | 2.0 | 0.08mm             |                            |
| 2404-13  | 4.0 | 1.5 | 4.0 | 0.8 | 405 | 2.4 | 2.0 | 0.08mm             | 25% 480 N/m<br>50% 710 N/m |
| 2404-14  | 4.0 | 1.5 | 5.8 | 0.8 | 610 | 2.4 | 2.0 | 0.08mm             | 25% 480 N/m<br>50% 710 N/m |
| 2404-16  | 9.7 | 1.5 | 5.6 | 1.8 | 610 | 4.2 | 3.8 | 0.08mm             | 25% 150 N/m<br>50% 330 N/m |

Material: Beryllium copper

## TWISTED FINGERSTRIPS 2403

2403-01

## COMBINATION WITH ENVIRONMENTAL RUBBER GASKET (ON REQUEST)

As an option, the 2400 series Twisted finger stock gasket can be combined with an environmental rubber gasket. This offers a high degree of protection against dust and moisture.

## ORDER EXAMPLE

**Part number**

Specify the part number that you need from the table