



CONDUCTIVE SILVER COATING 3830

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Detail : 3830 Conductive Silver Coating
 Application of the substance / the preparation: Surface Coating. For professional use only.
 Manufacturer / supplier: Holland Shielding Systems B.V.
 Jacobus Lipsweg 124
 3316 BP Dordrecht
 the Netherlands
 Ph: +31(0)78- 204 90 00
 Fax: +31(0)78- 204 90 08
 www.hollandshielding.com
 info@hollandshielding.com

NVIC Netherland, National Poison Information Center, Tel: +31 (0)30 2748888
 (in case of an emergency only to be reached by a medical person)

2. HAZARDS IDENTIFICATION

2.1 Classification of substance or mixture

Classification (CLP)

| | |
|--|------------|
| Flammable liquids | Category 2 |
| H225 Highly flammable liquid and vapor | |
| Serious eye irritation | Category 2 |
| H319 Causes serious eye irritation | |
| Specific target organ toxicity- single exposure | Category 3 |
| H335 May cause respiratory irritation | |
| Target organ: respiratory tract irritation | |
| Acute hazards to the aquatic environment | Category 1 |
| H400 Very toxic to aquatic life | |
| Chronic hazards to the aquatic environment | Category 1 |
| H410 Very toxic aquatic life with long lasting effects | |

2.2. Label elements

Label elements (CLP)

| | |
|-----------------------------------|--|
| Hazard pictogram | |
| Signal word | Danger |
| Hazard statement | H225 Highly flammable liquid and vapor H319 Causes serious eye irritation H335 May cause respiratory irritation H410 Very toxic to aquatic life with long lasting effects |
| Supplemental information | EUH066 Repeated exposure may cause skin dryness or cracking |
| Precautionary statement | P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources |
| Prevention | No smoking P260 Do not breathe mist/spray P280 Wear eye protection/face protection |
| Precautionary statement: Response | P370+P378 In case of fire: Use CO2, dry chemical, or foam for extinction |

2.3. Other hazards

None if used properly.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Base substances of preparation:

Pigment
Solvent

Revision date: 22-05-2015

www.hollandshielding.com

Jacobus Lipsweg 124, NL-3316 BP Dordrecht, The Netherlands
 Ph: +31(0)78 - 204 90 00
 Fax: +31(0)78 - 204 90 08
 info@hollandshielding.com
 hollandshielding.com

CONDUCTIVE SILVER COATING 3830

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. | EC Number REACH-Reg No. | Content | Classification |
|---|-------------------------------|---------|--|
| Methylisobutylketon 108-10-1 | 203-550-1 01-2119473980-30 | <60% | Flammable liquids 2 H225 Acute toxicity 4; Inhalation H332 Serious eye irritation 2 H319 STOT SE 3 H335 |
| Silver >: 99,9% Ag in powder (< 1 mm) 7440-22-4 | 231-131-3 | 25-50% | Aquatic Acute 1 H400 Aquatic Chronic 1 H410 M factor: 1.000 M factor (Chron Aquat Tox): 1.000 |
| Methanol 67-56-1 | 200-659-6 01-2119433307-44 | 0,1-1% | Flammable liquids 2 H225 STOT SE 1 H370 Acute toxicity 3; Inhalation H331 Acute toxicity 3; Dermal H311 Acute toxicity 3; Oral H301 |

For full text of the H- statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

4. FIRST AID MEASURES

4.1. Description of first aid measures

| | |
|--------------|---|
| Inhalation | Move to fresh air, consult doctor if complaint persists. |
| Skin contact | Rinse with running water and soap. In case of adverse health effects seek medical advice. |
| Eye contact | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| Ingestion | Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor. |

4.2. Most important symptoms and effects, both acute and delayed

Repeated exposure may cause skin dryness or cracking.

| | |
|-------------|---|
| EYE | Irritation, conjunctivitis. |
| RESPIRATORY | Irritation, coughing, shortness of breath, chest tightness. |

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures



CONDUCTIVE SILVER COATING 3830

5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder.
Fine water spray.

Extinguishing media which must not be used for safety reasons:

High pressure waterjet.

5.2. Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in fires.

5.3. Advice for firefighters

Wear protective equipment.
Wear self-contained breathing apparatus.

Additional information:

Cool endangered containers with water spray jet.

6. ACCIDENTAL RELEASE MEASURES

General information:

Danger of slipping on spilled product.

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Ensure that workrooms are adequately ventilated.
Avoid skin and eye contact.
See advice in section 8.
Avoid open flames and sources of ignition.
Ground/bond container and receiving equipment.
Use explosion proof electric equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.

Hygiene measures:

Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.
Temperatures between + 5 °C and + 30 °C.

7.3. Specific end use(s)

EMC product.

CONDUCTIVE SILVER COATING 3830

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational Exposure Limits

Valid for The Netherlands

| Ingredients | ppm | mg/m ³ | Type | Category | Remarks |
|--|-----|-------------------|-----------------------------------|-----------------------------------|---------|
| 4-methylpentaan-2-on 108-10-1 [4-METHYLPENTAAN-2-ON] | 20 | 83 | Time Weighted Average (TWA): | Indicative | ECLTV |
| 4-methylpentaan-2-on 108-10-1 [4-METHYLPENTAAN-2-ON] | 50 | 208 | Short Term Exposure Limit (STEL): | Indicative | ECLTV |
| 4-methylpentaan-2-on 108-10-1 [4-METHYLPENTAAN-2-ON] | | 104 | Time Weighted Average (TGG): | | NL OEL |
| 4-methylpentaan-2-on 108-10-1 [4-METHYLPENTAAN-2-ON] | | 208 | Permitted short-term | | NL OEL |
| Silver 7440-22-4 [SILVER, METALLIC] | | 0.1 | Time Weighted Average (TWA): | Indicative | ECLTV |
| Silver 7440-22-4 [SILVER, METALLIC] | | 0.1 | Time Weighted Average (TGG): | | NL OEL |
| Methanol 67-56-1 [METHANOL] | 200 | 260 | Time Weighted Average (TWA): | Indicative | ECLTV |
| Methanol 67-56-1 [METHANOL] | | 133 | Time Weighted Average (TGG): | | NL OEL |
| Methanol 67-56-1 [METHANOL] | | | Skin notation: | Can be absorbed through the skin. | NL OEL |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposed period | Value | | | | Remarks |
|---------------------------------|------------------------------|----------------|-------|-----|-------|------------|---------|
| | | | mg/l | ppm | mg/kg | others | |
| Methylisobutylketon 108-10-1 | Aqua (freshwater) | | | | | 0.6 mg/L | |
| Methylisobutylketon 108-10-1 | Aqua (marine water) | | | | | 0.06 mg/L | |
| Methylisobutylketon 108-10-1 | Sediment (freshwater) | | | | | 8.27 mg/kg | |
| Methylisobutylketon 108-10-1 | Sediment (marine water) | | | | | 0.83 mg/kg | |
| Methylisobutylketon 108-10-1 | Soil | | | | | 1.3 mg/kg | |
| Methylisobutylketon 108-10-1 | STP | | | | | 27.5 mg/L | |
| Methylisobutylketon 108-10-1 | Aqua (intermittent releases) | | | | | 1.5 mg/L | |
| Methanol 67-56-1 | Aqua (freshwater) | | | | | 20.8 mg/L | |
| Methanol 67-56-1 | Sediment (freshwater) | | | | | 77 mg/kg | |
| Methanol 67-56-1 | Aqua (marine water) | | | | | 2.08 mg/L | |
| Methanol 67-56-1 | Soil | | | | | 3.18 mg/kg | |
| Methanol 67-56-1 | STP | | | | | 100 mg/L | |
| Methanol 67-56-1 | Aqua (intermittent releases) | | | | | 1540 mg/L | |
| Methanol 67-56-1 | Sediment (marine water) | | | | | 7.7 mg/kg | |

CONDUCTIVE SILVER COATING 3830

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health effect | Exposure time | Value | Remarks |
|---------------------------------|--------------------|-------------------|---|---------------|-------------------|---------|
| Methylisobutylketon 108-10-1 | Worker | Inhalation | Acute/short term exposure- systemic effects | | 208 mg/m3 | |
| Methylisobutylketon 108-10-1 | Worker | Inhalation | Acute/short term exposure- systemic effects | | 208 mg/m3 | |
| Methylisobutylketon 108-10-1 | Worker | Inhalation | Long term exposure- systemic effects | | 83 mg/m3 | |
| Methylisobutylketon 108-10-1 | Worker | Inhalation | Long term exposure- systemic effects | | 83 mg/m3 | |
| Methylisobutylketon 108-10-1 | Worker | Dermal | Long term exposure- systemic effects | | 11.8 mg/kg bw/day | |
| Methylisobutylketon 108-10-1 | General population | Inhalation | Acute/short term exposure- systemic effects | | 155.2 mg/m3 | |
| Methylisobutylketon 108-10-1 | General population | Inhalation | Acute/short term exposure- systemic effects | | 155.2 mg/m3 | |
| Methylisobutylketon 108-10-1 | General population | Inhalation | Long term exposure- systemic effects | | 14.7 mg/m3 | |
| Methylisobutylketon 108-10-1 | General population | Inhalation | Long term exposure- systemic effects | | 14.7 mg/m3 | |
| Methylisobutylketon 108-10-1 | General population | Dermal | Long term exposure- systemic effects | | 4.2 mg/kg bw/day | |
| Methylisobutylketon 108-10-1 | General population | Oral | Long term exposure- systemic effects | | 4.2 mg/kg bw/day | |
| Methanol 67-56-1 | Worker | Dermal | Acute/short term exposure- systemic effects | | 40 mg/kg bw/day | |
| Methanol 67-56-1 | Worker | Inhalation | Acute/short term exposure- systemic effects | | 260 mg/m3 | |
| Methanol 67-56-1 | Worker | Inhalation | Acute/short term exposure- systemic effects | | 260 mg/m3 | |
| Methanol 67-56-1 | Worker | Dermal | Long term exposure- systemic effects | | 40 mg/kg bw/day | |
| Methanol 67-56-1 | Worker | Inhalation | Long term exposure- systemic effects | | 260 mg/m3 | |
| Methanol 67-56-1 | Worker | Inhalation | Long term exposure- systemic effects | | 260 mg/m3 | |
| Methanol 67-56-1 | General population | Dermal | Acute/short term exposure- systemic effects | | 8 mg/kg bw/day | |
| Methanol 67-56-1 | General population | Inhalation | Acute/short term exposure- systemic effects | | 50 mg/m3 | |
| Methanol 67-56-1 | General population | Oral | Acute/short term exposure- systemic effects | | 8 mg/kg bw/day | |
| Methanol 67-56-1 | General population | Inhalation | Acute/short term exposure- systemic effects | | 50 mg/m3 | |
| Methanol 67-56-1 | General population | Dermal | Long term exposure- systemic effects | | 8 mg/kg bw/day | |
| Methanol 67-56-1 | General population | Inhalation | Long term exposure- systemic effects | | 50 mg/m3 | |
| Methanol 67-56-1 | General population | Oral | Long term exposure- systemic effects | | 8 mg/kg bw/day | |
| Methanol 67-56-1 | General population | Inhalation | Long term exposure- systemic effects | | 50 mg/m3 | |

Biological exposure indices:
no

CONDUCTIVE SILVER COATING 3830

8.2. Exposure controls

| | |
|------------------------|---|
| Engineering controls | Ensure good ventilation/extraction. |
| Respiratory protection | In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter. This recommendation should be matched to local conditions. |
| Hand protection | Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Fluorinated rubber (FKM); >= 0.7 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Fluorinated rubber (FKM); >= 0.7 mm thickness This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (eg. temperature). If signs of wear and tear are noticed then the gloves should be replaced. |
| Eye protection | Tightly fitting safety goggles. |
| Skin protection | Wear suitable protective clothing. |

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

| | |
|--|-----------------------------------|
| Appearance | Liquid Liquid Silver |
| Odor | Solvent |
| Odor threshold | No data available/ Not applicable |
| pH | Not applicable |
| Initial boiling point | 116 °C (240.8 °F) |
| Flash point | 14 °C (57.2 °F) |
| Decomposition temperature | No data available/ Not applicable |
| Vapour (20 °C (68 °F)) | 7 mbar |
| Density (20 °C (68 °F)) | 1,34 g/cm ³ |
| Bulk density | No data available/ Not applicable |
| Viscosity (Brookfield; Instrument: RVT; 20 °C (68 °F); speed of rotation: 20 min ⁻¹) | 600- 1.200mPa.s |
| Viscosity (kinematic) | No data available/ Not applicable |
| Explosive properties | No data available/ Not applicable |
| Solubility (qualitative) (solvent: water) | Insoluble |
| Solidification temperature | No data available/ Not applicable |
| Melting point | No data available/ Not applicable |
| Flammability | No data available/ Not applicable |
| Auto-ignition temperature | No data available/ Not applicable |
| Explosive limits Lower Upper | 1,2%(V) 8,0%(V) |
| Partition coefficient: n-octanol/water | No data available/ Not applicable |
| Evaporation rate | No data available/ Not applicable |
| Vapor density | No data available/ Not applicable |
| Oxidising properties | No data available/ Not applicable |

9.2. Other information

No data available / Not applicable.

10. STABILITY AND REACTIVITY

10.1. Reactivity

Reaction with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity.

CONDUCTIVE SILVER COATING 3830

10.4. Conditions to avoid

No decomposition if used according to specifications.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None if used for intended purpose.

In case of fire toxic gases can be released.

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

| | |
|-----------------------------------|---|
| General toxicological information | The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex 1 to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following. |
| STOT-single exposure | May cause respiratory irritation. |
| Skin irritation | Repeated exposure may cause skin dryness or cracking. |
| Eye protection | Causes serious eye irritation. |

Acute oral toxicity

| Hazardous components CAS-No. | Value type | Value | Route of application | Exposure time | Species | Method |
|---|-------------------------------|---------------|----------------------|---------------|---------|--|
| Methylisobutylketon 108-10-1 | LD50 | 2.080 mg/kg | Oral | | Rat | OECD Guideline 401 (Acute Oral Toxicity) |
| Silver >= 99,9 % Ag in powder form (< 1 mm) 7440-22-4 | LD50 | > 2.000 mg/kg | Oral | | Rat | OECD Guideline 401 (Acute Oral Toxicity) |
| Methanol 67-56-1 | Acute toxicity estimate (ATE) | 100 mg/kg | Oral | | | Expert judgement |

Acute inhalative toxicity

| Hazardous components CAS-No. | Value type | Value | Route of application | Exposure time | Species | Method |
|------------------------------|-------------------------------|-----------------|----------------------|---------------|---------|--|
| Methylisobutylketon 108-10-1 | Acute toxicity estimate (ATE) | 11 mg/L | Inhalation | | | Expert judgement |
| Methylisobutylketon 108-10-1 | LD50 | 8.2 - 16.4 mg/L | Inhalation | 4 h | Rat | OECD Guideline 403 (Acute Inhalation Toxicity) |
| Methanol 67-56-1 | Acute toxicity estimate (ATE) | 3 mg/L | Inhalation | | | Expert judgement |

Acute dermal toxicity

| Hazardous components CAS-No. | Value type | Value | Route of application | Exposure time | Species | Method |
|------------------------------|------------|--------------|----------------------|---------------|---------|--|
| Methylisobutylketon 108-10-1 | LD50 | >2.000 mg/kg | Dermal | | Rat | OECD Guideline 402 (Acute Dermal Toxicity) |

Skin corrosion/irritation

| Hazardous components CAS-No. | Result | Exposure time | Species | Method |
|------------------------------|----------------|---------------|---------|--|
| Methylisobutylketon 108-10-1 | Not irritating | 4 h | Rabbit | OECD Guideline 404 (Acute Dermal Irritation/Corrosion) |
| Methanol 67-56-1 | Not irritating | | Rabbit | BASF Test |

CONDUCTIVE SILVER COATING 3830

Serious eye damage/irritation

| Hazardous components CAS-No. | Result | Exposure time | Species | Method |
|------------------------------|---------------------|---------------|---------|---|
| Methylisobutylketon 108-10-1 | Slightly irritating | | Rabbit | OECD Guideline 405 (Acute Eye Irritation/Corrosion) |
| Methanol 67-56-1 | Not irritating | | Rabbit | BASF Test |

Respiratory or skin sensitization

| Hazardous components CAS-No. | Result | Test type | Species | Method |
|------------------------------|-----------------|------------------------------|------------|---|
| Methylisobutylketon 108-10-1 | Not sensitising | Guinea pig maximisation test | Guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| Methanol 67-56-1 | Not sensitising | Guinea pig maximisation test | Guinea pig | Magnusson and Kligman Method |

Germ cell mutagenicity

| Hazardous components CAS-No. | Results | Type of study/ Route of administration | Metabolic activation/ Exposure time | Species | Method |
|------------------------------|----------|---|-------------------------------------|---------|---|
| Methylisobutylketon 108-10-1 | Negative | Bacterial reverse mutation assay (e.g. Ames test) | With and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |

Repeated dose toxicity

| Hazardous components CAS-No. | Results | Route of application | Exposure time/ Frequency of treatment | Species | Method |
|------------------------------|-----------------|----------------------|---------------------------------------|---------|--------|
| Methanol 67-56-1 | NOAEL=6.63 mg/L | Inhalation | 4 weeks 6 h/d, 5 d/w | Rat | |

12. ECOLOGICAL INFORMATION

| Hazardous components CAS-No. | Value type | Value | Acute Toxicity Study | Exposure time | Species | Method |
|------------------------------|------------|-------------|----------------------|---------------|--|--|
| Methylisobutylketon 108-10-1 | LD50 | 600 mg/L | Fish | 96 h | Salmo gairdneri (new name: Oncorhynchus mykiss) | OECD Guideline 203 (fish, Acute Toxicity Test) |
| Methylisobutylketon 108-10-1 | EC50 | 170 mg/L | Daphnia | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Methylisobutylketon 108-10-1 | EC50 | 400 mg/L | Algae | 96 h | Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition test) |
| Methanol 67-56-1 | NOEC | 7.900 mg/L | Fish | 200 h | Oryzias latipes | OECD 210 (fish early life stage toxicity test) |
| Methanol 67-56-1 | LC50 | >1.000 mg/L | Fish | 48 h | Leuciscus idus | DIN 38412-15 |
| Methanol 67-56-1 | EC50 | >10.00 mg/L | Daphnia | 48 h | Daphnia magna | |
| Methanol 67-56-1 | EC50 | 28.44 mg/L | Algae | | Chlorella pyrenoidosa | OECD Guideline 201 (Alga, Growth Inhibition Test) |

12.2. Persistence and degradability

| Hazardous components CAS-No. | Result | Route of application | Degradability | Method |
|------------------------------|-----------------------|----------------------|---------------|--|
| Methylisobutylketon 108-10-1 | Readily biodegradable | Aerobic | 99% | OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test) |
| Methanol 67-56-1 | Readily biodegradable | Aerobic | 82 - 92% | EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test) |



CONDUCTIVE SILVER COATING 3830

12.3. Bioaccumulative potential / 12.4. Mobility in soil

| Hazardous components CAS-No. | LogKow | Bioconcentration factor _BCF) | Exposure time | Species | Temperature | Method |
|---------------------------------|--------|----------------------------------|------------------|---------|-------------|--------|
| Methylisobutylketon 108-10-1 | 1.31 | | | | 20°C | |
| Methanol 67-56-1 | -0.77 | | | | | |

12.5. Results of PBT and vPvB assessment

| Hazardous components CAS-No. | PBT/vPvB |
|--|---|
| Methylisobutylketon 108-10-1 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Silver >: 99,9% Ag in powder (< 1 mm) 7440-22-4 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Methanol 67-56-1 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Other adverse effects

No data available.

13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product disposal

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

080111

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

14. TRANSPORT INFORMATION

14.1. UN number

| | |
|------|------|
| ADR | 1263 |
| RID | 1263 |
| ADN | 1263 |
| IMDG | 1263 |
| IATA | 1263 |

14.2. UN proper shipping name

| | |
|------|----------------|
| ADR | PAINT |
| RID | PAINT |
| ADN | PAINT |
| IMDG | PAINT (Silver) |
| IATA | PAINT |

14.3 Transport hazard class(es)

| | |
|------|---|
| ADR | 3 |
| RID | 3 |
| ADN | 3 |
| IMDG | 3 |
| IATA | 3 |

CONDUCTIVE SILVER COATING 3830

14.4 Packaging group

| | |
|------|----|
| ADR | II |
| RID | II |
| ADN | II |
| IMDG | II |
| IATA | II |

14.5 Environmental hazards

| | |
|------|---------------------------|
| ADR | Environmentally Hazardous |
| RID | Environmentally Hazardous |
| ADN | Environmentally Hazardous |
| IMDG | Environmentally Hazardous |
| IATA | Not applicable |

14.6 Special precautions for user

| | |
|------|--|
| ADR | Special provision 640D Tunnelcode: (D/E) |
| RID | Special provision 640D |
| ADN | Special provision 640D |
| IMDG | Not applicable |
| IATA | Not applicable |

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content 52.6 %
(EC)

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out.

16. OTHER INFORMATION

The labeling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

| | |
|------|--|
| H225 | Highly flammable liquid and vapor |
| H301 | Toxic if swallowed |
| H311 | Toxic in contact with skin |
| H319 | Causes serious eye irritation |
| H331 | Toxic if inhaled |
| H332 | Harmful if inhaled |
| H335 | May cause respiratory irritation |
| H370 | Causes damage to organs |
| H400 | Very toxic to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects |

Further information

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.